

Battery rating	Capacity ah @ 20hrs	Dimensions			Constant current discharge rating - amperies at 27 C (10.5 EMV)										Terminal Type
		length	width	Total height	Approx weight	10 Min	15 Min	30 Min	60 Min	2 Hrs	3 Hrs	5 Hrs	10 Hrs	20 Hrs	
12 v 26 AH	26	167	126	175	9	53.06	41.94	25.74	16.25	9.29	6.57	4.44	2.42	1.3	L terminal (B5)
12 v 42 AH	42	199	167	175	14	85.71	67.74	41.58	26.25	15	10.61	7.18	3.91	2.1	L terminal (B6)
12 v 65 AH	65	351	167	175	20	114.29	90.32	55.45	35	20	14.14	10.3	5.59	3.25	L terminal (B6)
12 v 84 AH	84	351	167	203	27	171.43	135.5	83.17	52.5	30	21.21	14.4	7.82	4.2	L terminal (B6)
12 v 100 AH	100	393	173	221	32.5	200	158.7	98	61	35.7	25.25	17.1	9.31	5	MB X 25 mm Copper
12 v 120 AH	120	393	173	240	36.6	240	190.5	117.7	73.17	42.9	30.3	20.5	11.17	6	MS X 25 mm Copper
12 v 130 AH	130	445	168	247	42	265.31	209.7	128.7	81.25	46.4	32.83	22.2	12.1	6.5	L terminal (B6)
12 v 150 AH	150	453	173	251	45	300	238.1	147.1	91.46	53.6	37.88	25.6	13.97	7.5	MB X 25 mm Copper
12 v 160 AH	160	445	168	283	52	326.53	258.1	158.4	100	57.1	40.4	27.4	14.9	8	L terminal (B6)
12 V 200 AH	200	556	186	263	62	400	317.5	196.1	122	71.4	50.5	34.2	18.6	10	MB X 25 mm Copper